







GT960 **KDI**<http://tiny.cc/multioneGT960EN>
**KOHLER**  
 ENGINES


|  |  |   |  |  |
|--|--|---|--|--|
| <br>TIPPING LOAD<br><b>1960</b><br>kg | <br>ENGINE POWER<br><b>58</b><br>hp | <br>SPEED<br><b>30</b><br>km/h | <br>FLOW RATE<br><b>95</b><br>l/min | <br>LIFT HEIGHT<br><b>3,15</b><br>m |
|--|--|---|--|--|

| Tires size  | Width             |
|-------------|-------------------|
| 27x8.50-15  | 1070 mm (42.1 in) |
| 26x12.00-12 | 1290 mm (50.8 in) |
| 29x12.50-15 | 1450 mm (57.1 in) |
| 31x15.50-15 | 1490 mm (58.7 in) |

| Model   | GT960 <b>KDI</b>                     |
|---|--------------------------------------|
| Engine  | Kohler 1903 TCR                      |
| Power (Iso Gross)                                 | 58 HP                                |
| Fuel  | Diesel                               |
| Transmission                                      | Hydrostatic                          |
| Drive speed (max.) 2 speed                        | 15-30 km/h (9.3-18.6 mph)            |
| Aux. hydraulics oil flow                          | 95 l/min (25 gal/min)                |
| Max. lifting height                               | 3,15 m (124 in)                      |
| Tipping load, max <sup>(1)</sup>                  | 1960 kg (4321 lbs)                   |
| Lifting capacity straight <sup>(2)</sup>          | 1570 kg (3461 lbs)                   |
| Lifting capacity fully articulated <sup>(3)</sup> | 1400 kg (3086 lbs)                   |
| Breakout force / 50 cm (19.7 in)                  | 1600 kg (3530 lbs)                   |
| Pushing force (c)                                 | 1800 kgf (1800 kp)                   |
| Specific ground pressure (w/standard tires)       | 776 kg/m <sup>2</sup> (159 lbs/sqft) |
| Turning radius: inside/outside                    | 1000/2490 mm (39.4/98 in)            |
| Standard tires (Tractor profile)                  | 31x15.50-15 (400/50-15)              |
| Length  | 2900 mm (114.2 in)                   |
| Height  | 2176 mm (85.7 in)                    |
| Weight  | 1700 kg (3748 lbs)                   |
| Product Code                                      | <b>C981000</b>                       |
| Price   |                                      |



(<sup>1</sup>) Maximum load that can be lifted just off the ground when the machine is straight, with backweights and boom not extended. Weight of attachment included.  
 (<sup>2</sup>) Machine straight, with backweights and boom not extended. Weight of attachment is included.(80% of tipping load).  
 (<sup>3</sup>) Machine fully articulated, with backweights and boom not extended. Weight of attachment is included.

**MULTI**1**ONE**

## GT960 **KDI** FEATURES AND OPTIONS

- New Turbo Common Rail Kohler engine (TIER 4 Final)
- 4WD hydrostatic Direct Drive motors, 2 speed
- DBS (Dynamic Block System)
- Hydraulic oil cooler
- Hydraulic multiconnector
- Double-H frame telescopic boom
- 11-functions joystick
- ROPS-FOPS Level I
- LCD graphic display with service light (tachometer, hour meter, fuel gauge, maintenance light, light indicator and other 14 indicators)
- 2 front working light
- Ergonomic full adjustable suspension seat with armrests and safety belt.
- Tipping sensor
- Multi-disk parking brake

| Suggested configurations | Description   | Price |
|--------------------------|---|-------|
| PRIME                    | Self-levelling  |       |
| WINTER                   | Self-levelling, floating boom valve, Luxury cab (glass) with heating system, heated seat, inner clothing, engine block heater |       |
| ON-ROAD                  | Self-levelling, floating boom valve, road lights, trailer coupling  |       |
| DELUXE                   | Self-levelling, floating boom valve, Luxury cab (glass) with heating system, automatic locking/unlocking plate                |       |

## GT960 **KDI** FEATURES AND OPTIONS

| Options  | Code    | Price |
|--|---------|-------|
| Self-levelling kit                               | C885030 |       |
| Floating boom valve                              | C885024 |       |
| Luxury cabin (glass) with heating system         | C885003 |       |
| Heating system                                   | C885029 |       |
| Smart cabin                                      | C885043 |       |
| Road lights                                      | C885032 |       |
| Automatic locking plate                          | C885038 |       |
| Multi connector "After Market" assembling        | C880217 |       |
| Multiconnector to quick coupling 3 lines adapter | C880221 |       |
| Heated seat                                      | C885015 |       |
| Trailer coupling                                 | C885017 |       |
| Integrated backweight 100 kg (220 lbs)           | C885031 |       |
| Additional backweights 440 kg (970 lbs)          | C885025 |       |
| Driver area cover                                | C880049 |       |
| FOPS front end protection, level 1               | C885021 |       |
| Inner clothing for cabin                         | C885040 |       |
| Air conditioning                                 | C885036 |       |
| Left protection bar for operator                 | C885009 |       |
| Rear hydraulic outlets                           | C885252 |       |
| Torque divider                                   | C885253 |       |
| Skid profile tires 27x8.50-15, set of 4          | C885210 |       |
| Turf profile tires 29x12.50-15, set of 4         | C885212 |       |
| Wheel spacer 10 mm (2.2 in), max 1 pc for wheel  | C880090 |       |
| Snow chains for wheels, 31x15.50-15, set of 2    | C880044 |       |
| Snow chains for wheels 27x8.50-15, set of 2      | C880045 |       |
| Engine block heater 220 V                        | C885250 |       |
| Engine block heater 110 V                        | C885255 |       |
| Back up alarm                                    | C883021 |       |
| Beacon light                                     | C883039 |       |